

date 15.02.2024

DATASHEET

Reg. No. **011-6T0044**

(filled in by DIN CERTCO)

Thermostatic radiator valves according to DIN EN 215

Certificate Holder	Schneider Electric Controls UK Ltd		ID 15
Street, number	401 Southway Drive		
Postal code / City	Plymouth PL6 6QT		
Country	UNITED KINGDOM		
Head	TRV4		
Type	Liquid	Head with integral sensor	
Hysteresis C	0,40 K	Differential pressure influence <i>D</i>	0,15 K
Response time Z	20 min.	Water temperature effect <i>W</i>	0,80 K
Control accuracy CA	0,60 K		
Head	TRV4 Remote		
Type	Liquid	Head with remote sensor and with remote sensor	
Hysteresis C	0,60 K	Differential pressure influence <i>D</i>	0,10 K
Response time Z	20 min.	Water temperature effect <i>W</i>	0,40 K
Control accuracy CA	0,60 K		
	TRV4 all white		
Type	Liquid	Head with integral sensor	
Hysteresis C	0,40 K	Differential pressure influence <i>D</i>	0,15 K
Response time Z	20 min.	Water temperature effect <i>W</i>	0,80 K
Control accuracy CA	0,60 K		
	RT212		
Type	Liquid	Head with integral sensor	
Hysteresis C	0,45 K	Differential pressure influence <i>D</i>	0,15 K
Response time Z	20 min.	Water temperature effect <i>W</i>	0,90 K
Control accuracy CA	0,60 K		
	RT414		
Type	Liquid	Head with integral sensor	
Hysteresis C	0,35 K	Differential pressure influence <i>D</i>	0,15 K
Response time Z	22 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy CA	0,60 K		

Valve(s)	Series	Form ¹	Size	Nominal flow rate ²
1 Form: 2 Nominal flow rate $q_{n\text{ NH}}$ in kg/h:	L – Angle declared by the manufacturer	T – Straight		
EB 15 mm Angle	GB	L	DN 15	175
EB 15 mm Straight	GB	T	DN 15	172
EB 1/2 Angle	D	L	DN 15	175
EB 1/2 Straight	D	T	DN 15	172
EB 3/4 Angle	D	L	DN 20	208
EB 3/4 Straight	D	T	DN 20	208
ED 15 mm Angle	*	L	DN 15	205
ED 15 mm Straight	*	T	DN 15	205