TÜVRheinland®
DIN CERTCO

itw

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S074 R
	Date of issue	09.07.2009

Company	Consolar Solare Energiesysteme GmbH	**Country**		Deutschland
Brand (optional)		**Website**		www.consolar.com
Street, number	Gewerbestrasse 7	**E-mail**		ulrich.leibfried@consolar.de
Postal Code	79539	**Tel.**	+49	7621 42228 34
City	Lörrach	**Fax**	+49	7621 42228 31

Collector Type (flat plate / evacuate tubular / un-glazed)	Evacuated tubular collector
Integration in the roof possible ?	No

Collector name	Aperture area (Aa) [m²]	Gross length [mm]	Gross width [mm]	Gross height [mm]	Gross area (AG) [m²]	Power output per collector unit G = 1000 W/m², Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
TUBO 12 CL	0.99	1.885	625	60	1.18	614	608	584	545	489
T12	0.99	1.885	625	60	1.18	614	608	584	545	489

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.620	-
	a_{1a}	0.395	W/(m²K)
	a_{2a}	0.020	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	248	°C
Effective thermal capacity	$c_{eff} = C/A_a$	13.84	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	1000	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	G_{DIF}/G_{TOT} max	θ_T / θ_L	50°	*10°*	*20°*	*30°*	*40°*	*60°*	*70°*
	-	-	$K_\theta(\theta_T)$	1.04	1.00	0.99	1.02	1.03	1.15	1.35
			$K_\theta(\theta_L)$	0.95	1.00	1.00	0.99	0.98	0.89	0.76

G_{DIF}/G_{TOT}: min&max - while measuring — ***Optional values***

Testing Laboratory	TZS, ITW University of Stuttgart
Website	www.tzs.uni-stuttgart.de
Test report id. number	06COL457/1
Date of test report	09.07.2009
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :

Note 1	**Fluid**	Water	**Flow rate**	0.017	kg/s per m²
Note 2	**Irradiance, Gs=1000 W/m²** **Ambient temperature , Ta=30 °C**				
Note 3	**Given by manufacturer**				

TZS Forschungs- und Testzentrum für Solaranlagen
Institut für Thermodynamik und Wärmetechnik
Universität Stuttgart
Pfaffenwaldring 6, 70550 Stuttgart (Vaihingen)

VERSION 3.6, 2012.01.13

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S074 R
	Issued	09.07.2009

Annual collector output kWh

Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
TUBO 12 CL	1.080	976	798	1.006	864	668	682	573	432	732	619	468
T12	1.080	976	798	1.006	864	668	682	573	432	732	619	468

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1.765	18.5	South, 25°
Davos	47	1.714	3.2	South, 30°
Stockholm	59	1.166	7.5	South, 45°
Würzburg	50	1.244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.6, 2012.01.13
Calculation program version:
3.07, October 2011 (SP)