


| | | | | | | | | | | | | | | | |
|--|---|--------------|--|--------------|--------------|---|----------------------|--|----------------------------|----------------------------|-------------------|-------------|-------------|-------------|-------------|
| Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate | | | | | | Licence Number | | 011-7S2120 F | | | | | | | |
| | | | | | | Issued | | 2015-11-09 | | | | | | | |
| Company holding the | | | B&S Wärmetechnik und Wohnen | | | Country | | Deutschland | | | | | | | |
| Brand (optional) | | | Reinhard Bege | | | Website | | www.waerme-wohnen.de | | | | | | | |
| Street, street number | | | Theresienstraße 1 | | | E-mail | | mail@waerme-wohnen.de | | | | | | | |
| Postal Code / City, province | | | 85399 Hallbergmoos | | | Tel/Fax | | +49 81 199 632 580 / 81 194 206 | | | | | | | |
| Collector Type (flat plate glazed/un-glazed; evacuate tubular) | | | | | | Flat plate collector - glazed | | | | | | | | | |
| Thermal / photo voltaic hybrid collector? (PVT collector) | | | | | | No | | | | | | | | | |
| Integration in the roof possible ? (manufacturers declaration) | | | | | | Yes | | | | | | | | | |
| | | | | | | Power output per collector module | | | | | | | | | |
| | | | | | | G = 1000 W/m² | | | | | | | | | |
| | | | | | | Tm-Ta | | | | | | | | | |
| | | | | | | 0 K | 10 K | 30 K | 50 K | 70 K | | | | | |
| Collector name | | | | | | W | W | W | W | W | | | | | |
| BS Solid Green SS20* | | | | | | 1 507 | 1 433 | 1 272 | 1 092 | 894 | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| Performance test method | | | | | | Glazed liquid heating collector - steady state - outdoor | | | | | | | | | |
| Performance parameters related to aperture area | | | | | | η_0 | a1 | a2 | | | | | | | |
| Units | | | | | | - | W/(m ² K) | W/(m ² K ²) | | | | | | | |
| Test results - Flow rate and fluid see note 1 | | | | | | 0.785 | 3.722 | 0.012 | | | | | | | |
| Bi-directional incidence angle modifiers? | | | | | | No | | | | | | | | | |
| | | | | | | <i>Kθ values are obligatory for 50°.</i> | | | | | | | | | |
| Incidence angle modifiers Kθ(θ) | | | | | | Angle | 10° | 20° | 30° | 40° | 50° | 60° | 70° | 80° | 90° |
| | | | | | | Kθ(θ) | 1.00 | 0.99 | 0.98 | 0.97 | 0.94 | 0.90 | 0.80 | 0.51 | 0.00 |
| Incidence angle modifier not bi-directional - leave fields blank | | | | | | | | | | | | | | | |
| Stagnation temperature - Weather conditions see note 2 | | | | | | Tstg | | 203 | | °C | | | | | |
| Effective thermal capacity | | | | | | ceff = C/AAp | | 9.543 | | kJ/(m²K) | | | | | |
| Max. intende operation temperature - see note 3 | | | | | | Tmax,op | | - | | °C | | | | | |
| Max. operation pressure - see note 3 | | | | | | pmax,op | | 1000 | | kPa | | | | | |
| Pressure drop table - for a collector family, the values shall be for the module with highest ΔP per m² aperture area | | | | | | | | | | | | | | | |
| Flow rate | kg/(s m ²) | - | - | - | - | - | - | - | - | - | | | | | |
| Pressure drop, ΔP | Pa | - | - | - | - | - | - | - | - | - | | | | | |
| Optional weather data | | | | | | Location | | | | Link | | | | | |
| Testing Laboratory | | | | | | TZS, ITW University Stuttgart | | | | | | | | | |
| Website | | | | | | http://www.itw.uni-stuttgart.de | | | | | | | | | |
| Test report id. number | | | | | | 12COL1079OEM08, 12COL1079QOEM08 | | | Date of test report | | 2013.03.25 | | | | |
| During the test GDIF/GTOT was always between | | | | | | 0 | and | 1 | | | | | | | |
| Comments of testing laboratory: | | | | | | | | | | | | | | | |
| <i>* dimensions according to manufacturer</i> | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| Note 1 | Flow rate | 0.020 | kg/(s m ²) | Fluid | Water | | | | | | | | | | |
| Note 2 | Irradiance, G = 1000 W/m²; Ambient temperature , Ta=30 °C | | | | | | | | | | | | | | |
| Note 3 | Given by manufacturer | | | | | | | | | | | | | | |
|  Forschungs- und Testzentrum für Solaranlagen Institut für Thermodynamik, Fluidmechanik und Wärmeübertragung Universität Stuttgart Pfaffenwaldring 6, 70509 Stuttgart (Vollring) | | | | | | | | | | | | | | | |
| Datasheet version: 4.06, 2014-01-15 | | | | | | | | | | | | | | | |
| DIN CERTCO • Albainstraße 56 • 12103 Berlin Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de | | | | | | | | | | | | | | | |

| | | |
|---|----------------|--------------|
| Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate | Licence Number | 011-7S2120 F |
| | Issued | 09.11.2015 |

| Annual collector output kWh/module | | | | | | | | | | | | | | | |
|------------------------------------|--|-------|-------|-------|-------|------|-----------|------|------|----------|------|------|--|--|--|
| Collector name | Location and collector temperature (T _m) | | | | | | | | | | | | | | |
| | Athens | | | Davos | | | Stockholm | | | Würzburg | | | | | |
| | 25°C | 50°C | 75°C | 25°C | 50°C | 75°C | 25°C | 50°C | 75°C | 25°C | 50°C | 75°C | | | |
| BS Solid Green SS20* | 2 403 | 1 715 | 1 126 | 1 824 | 1 263 | 799 | 1 344 | 880 | 535 | 1 461 | 951 | 569 | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |

| | |
|---------------------------------------|---|
| Collector mounting: Fixed or tracking | Fixed; slope = latitude - 15° (rounded to nearest 5°) |
|---------------------------------------|---|

| Overview of locations | | | | |
|-----------------------|------------|--|----------------------|--|
| Location | Latitude ° | G _{tot} kWh/m ² | T _a °C | Collector orientation or tracking mode |
| Athens | 38 | 1 765 | 18.5 | South, 25° |
| Davos | 47 | 1 714 | 3.2 | South, 30° |
| Stockholm | 59 | 1 166 | 7.5 | South, 45° |
| Würzburg | 50 | 1 244 | 9.0 | South, 35° |
| | | | | |
| | | | | |
| | | | | |

| | | |
|------------------|--|--------------------|
| G _{tot} | Annual total irradiation on collector plane | kWh/m ² |
| T _a | Mean annual ambient air temperature | °C |
| T _m | Constant collector operating temperature (mean of in- and outlet temperatures) | °C |

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (T_m). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.