

Annex to Solar Keymark Certificate Supplementary Information	Licence Number	011-7S3010 F
	Issued	2021-04-12

Annual collector output in kWh/collector at mean fluid temperature ϑ_m													
Collector name	Standard Locations ϑ_m	Athens			Davos			Stockholm			Würzburg		
		25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
Solarwerk 21plus		2,662	1,964	1,335	2,057	1,464	951	1,513	1,022	640	1,647	1,112	684
Solarwerk 26plus		3,386	2,498	1,698	2,617	1,862	1,209	1,924	1,300	814	2,094	1,414	870
Annual output per m ² gross area		1,292	953	648	999	711	462	734	496	311	799	540	332
Annual efficiency, η_a		73%	54%	37%	61%	44%	28%	63%	43%	27%	64%	43%	27%
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		

The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Ver. 6.1 (July 2019). A detailed description of the calculations is available at <http://www.estif.org/solarkeymarknew/>

Additional Information					
Collector heat transfer medium	Water-Glycole				
The collector is deemed to be suitable for roof integration	Yes				
The collector was tested successfully under the following conditions:					
Climate class (A+, A, B or C)	A		--		
G (W/m ²) >	1000	ϑ_a (°C) >	20	H _x (MJ/m ²) >	600
Maximum tested positive load	2400		Pa		
Maximum tested negative load	2400		Pa		
Hail resistance using ice balls (diameter)	45		mm		

Additional collector attribute(s)			
<input type="checkbox"/> Using external power source(s) for normal operation	<input type="checkbox"/> Active or passive measure(s) for self-protection		
<input type="checkbox"/> Co-generating thermal and electrical power	<input type="checkbox"/> Façade collector(s)		

Energy Labelling Information		Additional Informative Technical Data	
	Reference Area, A _{sol} (m ²)	Hydraulic Designation Code	Aperture Area, A _a (m ²)
Solarwerk 21plus	2.06	11-V-1234S-A:6,1905-C:18,1052-D	1.93
Solarwerk 26plus	2.62	14-V-1234S-A:6,1905-C:18,1328-D	2.47

Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}		Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}	
Collector efficiency (η_{col})	64%	Zero-loss efficiency (η_0)	0.79
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		First-order coefficient (a ₁)	3.34
		Second-order coefficient (a ₂)	0.014
		Incidence angle modifier IAM (50°)	0.94
		Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.	