TÜVRheinland®
DIN CERTCO

SPF Solartechnik Prüfung Forschung

Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate	**Certificate No.**	**011-7S180 F**
	Date of issue	26.01.2012

Company	HEWALEX Sp. z o.o. Sp. k.	**Country**		Poland
Brand (optional)	--	**Website**		www.hewalex.eu
Street, number	ul. Juliusza Slowackiego, 33	**E-mail**		hewalex@hewalex.pl
Postal Code	PL-43-502	**Tel.**	+48	32 214 17 10
City	Czechowice-Dziedzice	**Fax**	+48	32 214 50 04

Collector Type (flat plate / evacuate tubular / un-glazed)	Flat plate collector
Integration in the roof possible ?	Yes

Collector name	**Aperture area (Aa)** [m²]	**Gross length** [mm]	**Gross width** [mm]	**Gross height** [mm]	**Gross area (A_G)** [m²]	**Power output per collector unit** G = 1000 W/m² Tm-Ta : 0 K [W]	10 K [W]	30 K [W]	50 K [W]	70 K [W]
KS2000 SLP; KS2000 SP	1.817	2'019	1'037	90	2.094	1'474	1'391	1'215	1'025	821

Collector efficiency parameters related to aperture area (Aa) Type of fluid and flow rate see note 1	η_{0a}	0.811	-
	a_{1a}	4.46	W/(m²K)
	a_{2a}	0.0096	W/(m²K²)
Stagnation temperature - Weather conditions see note 2	t_{stg}	192	°C
Effective thermal capacity	$c_{eff} = C/A_a$	5.7	kJ/(m²K)
Max. operation pressure - see note 3	p_{max}	600	kPa

Incidence angle modifiers $K_\theta(\theta)$	G_{DIF}/G_{TOT} min	G_{DIF}/G_{TOT} max	θ_T / θ_L	50°	*10°*	*20°*	*30°*	*40°*	*60°*	*70°*
	0.1	0.25	$K_\theta(\theta_T)$	0.93	*1.00*	*1.00*	*0.99*	*0.97*	*0.85*	*0.71*
			$K_\theta(\theta_L)$	0.93	*1.00*	*1.00*	*0.99*	*0.97*	*0.85*	*0.71*
G_{DIF}/G_{TOT}: min&max - while measuring					***Optional values***					

Testing Laboratory	SPF, CH-8640 Rapperswil
Website	www.solarenergy.ch
Test report id. number	C824LPEN-A1, C824QPEN-A1
Date of test report	24.01.2012 / 24.01.2012
Perf. test method	EN 12975-2 6.1.4 (outdoor)

Comments of testing laboratory :

The only difference between the SLP and SP collectors is the casing coated in RAL7022 (Umbra grey).

Note 1	**Fluid**	Water-Glycole	**Flow rate**	0.026	kg/s per m²	
Note 2	**Irradiance, Gs=1000 W/m²** **Ambient temperature , Ta=30 °C**					
Note 3	**Given by manufacturer**					

Dr. Andreas Bohren



VERSION 3.5, 2012.01.13

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

TÜVRheinland®
DIN CERTCO

SPF Solartechnik Prüfung Forschung

Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Certificate No.	011-7S180 F
	Issued	26.01.2012

Annual collector output kWh

Collector name	Location and collector temperature (Tm)											
	Athens			Davos			Stockholm			Würzburg		
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
KS2000 SLP; KS2000 SP	2'321	1'585	996	1'841	1'217	734	1'268	795	466	1'381	856	493

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)

Overview of locations

Location	Latitude °	Gtot kWh/m²	Ta °C	Collector orientation or tracking mode
Athens	38	1'765	18.5	South, 25°
Davos	47	1'714	3.2	South, 30°
Stockholm	59	1'166	7.5	South, 45°
Würzburg	50	1'244	9.0	South, 35°

Gtot	Annual total irradiation on collector plane	kWh/m²
Ta	Mean annual ambient air temperature	°C
Tm	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

Calculation of the annual collector performance is done by the official Solar Keymark spreadsheet tool. Hour by hour the collector output is calculated according to the efficiency parameters from the Keymark test using constant collector operating temperature (Tm). Detailed description with all equations used is available from the Solar Keymark web site (direct link: http://www.estif.org/solarkeymark/annexb1.php)

DIN CERTCO ● Alboinstraße 56 ● 12103 Berlin
Tel: +49 30 7562-1131 ● Fax: +49 30 7562-1141 ● E-Mail: info@dincertco.de ● www.dincertco.de

Datasheet version:
VERSION 3.5, 2012.01.13
Calculation program version:
3.07, October 2011 (SP)