

DATASHEET

Reg. No. **011-6T0037**

(filled in by DIN CERTCO)

Thermostatic radiator valves according to DIN EN 215

Certificate Holder	Hangzhou DOZ Import & Export Co., Ltd.	ID 74
---------------------------	---	--------------

Street, number Room 302, Binke Mansion; 1503 Xipu Road

Postal code / City 310053 Hangzhou

Country People's Republic of China

Head TRCD07

Type	Liquid	Head with integral sensor	
Hysteresis C	0,30 K	Differential pressure influence D	0,20 K
Response time Z	23 min.	Water temperature effect W	1,20 K
Control accuracy CA	0,60 K		

Head TRCD07C

Type	Liquid	Head with integral sensor	
Hysteresis C	0,70 K	Differential pressure influence D	0,30 K
Response time Z	23 min.	Water temperature effect W	1,20 K
Control accuracy CA	1,00 K		

Head TRCD09

Type	Liquid	Head with integral sensor	
Hysteresis C	0,30 K	Differential pressure influence D	0,20 K
Response time Z	23 min.	Water temperature effect W	1,20 K
Control accuracy CA	0,60 K		

Head TRCD09C

Type	Liquid	Head with integral sensor	
Hysteresis C	0,70 K	Differential pressure influence D	0,30 K
Response time Z	23 min.	Water temperature effect W	1,20 K
Control accuracy CA	1,00 K		

Head Jaga H01

Type	Liquid	Head with integral sensor	
Hysteresis C	0,60 K	Differential pressure influence D	0,15 K
Response time Z	10 min.	Water temperature effect W	1,20 K
Control accuracy CA	1,00 K		

Head		TRCD16	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,30 K	Differential pressure influence <i>D</i>	0,20 K
Response time <i>Z</i>	23 min.	Water temperature effect <i>W</i>	1,20 K
Control accuracy <i>CA</i>	0,60 K		
Head		CRB 01SA 006	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,70 K	Differential pressure influence <i>D</i>	0,20 K
Response time <i>Z</i>	27 min.	Water temperature effect <i>W</i>	1,20 K
Control accuracy <i>CA</i>	1,00 K		
Head		CRB 01SA 006-A	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,45 K	Differential pressure influence <i>D</i>	0,10 K
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	1,20 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD10	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD10C	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD10W	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD10G	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		

Head		TRCD10B	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD10CB	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD25	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,60 K	Differential pressure influence <i>D</i>	0,15 K
Response time <i>Z</i>	28 min.	Water temperature effect <i>W</i>	0,80 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD25C	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,15 K
Response time <i>Z</i>	28 min.	Water temperature effect <i>W</i>	0,90 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD33	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,25 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD33G	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,25 K
Response time <i>Z</i>	20 min.	Water temperature effect <i>W</i>	1,00 K
Control accuracy <i>CA</i>	0,60 K		
Head		TRCD05	
Type	Liquid	Head with integral sensor	
Hysteresis <i>C</i>	0,55 K	Differential pressure influence <i>D</i>	0,25 K
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	0,75 K
Control accuracy <i>CA</i>	0,60 K		

Head		TRCD34			
Type	Liquid	Head with integral sensor			
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K		
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	0,80 K		
Control accuracy <i>CA</i>	0,60 K				
Head		TRCD34C			
Type	Liquid	Head with integral sensor			
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,30 K		
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	0,80 K		
Control accuracy <i>CA</i>	0,60 K				
Head		TS202			
Type	Liquid	Head with integral sensor			
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,20 K		
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	1,00 K		
Control accuracy <i>CA</i>	0,60 K				
Head		TS206			
Type	Liquid	Head with integral sensor			
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,20 K		
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	1,00 K		
Control accuracy <i>CA</i>	0,60 K				
Head		TS207W			
Type	Liquid	Head with integral sensor			
Hysteresis <i>C</i>	0,50 K	Differential pressure influence <i>D</i>	0,20 K		
Response time <i>Z</i>	25 min.	Water temperature effect <i>W</i>	1,00 K		
Control accuracy <i>CA</i>	0,60 K				
Valve(s)	Series	Form¹	Size	Nominal flow rate²	
1 Form:		L – Angle		T – Straight	
2 Nominal flow rate $q_{n,NH}$ in kg/h:		declared by the manufacturer			
C04059H063B	GB	L	DN 15	140	
CL04017H002B4	*	T	DN 15	120	
L04017N007B4	GB	L	DN 15	140	
L04017N006B4	*	T	DN 15	120	
Jaga V01	*	L	DN 15	188	
CVB 04TE 014	*	L	DN 15	180	

CVB 04TE 013	*	T	DN 15	165
C04169H407B	*	L	DN 15	195/185
C04169H406B	*	L	DN 15	170
C04169H405B	*	T	DN 15	175
C04167H407B	*	T	DN 15	198
C04169H446B	*	L	DN 15	140
C04169H447B	*	T	DN 15	145
C04167N057B	GB	T	DN 15	190/160
C04169H722C	-	L	DN 15	185
C04169H723C	-	T	DN 15	185
C04167N075B4		L	DN 10	180
C04167N076B		T	DN 10	180