



Summary of EN 12975 Test Results, annex to Solar KEYMARK Certificate							Licence Number		011-7S2615 F				
							Issued		2015-12-02				
Company holding the licence		Ariston Thermo S.p.A.					Country		Italy				
Brand (optional)		Ariston					Website		www.aristonthermo.com				
Street, street number		Via A. Merloni 45					E-mail		public.relations@aristonthermo.com				
Postal Code / City, province		60044		Fabriano			Tel/Fax		39 02763209 -1 / -40				
Collector Type (flat plate glazed/un-glazed; evacuate tubular)							Flat plate collector - glazed						
Thermal / photo voltaic hybrid collector? (PVT collector)							No						
Integration in the roof possible? (manufacturers declaration)							No						
Collector name	Aperture area (Aa) m <sup>2</sup>	Gross length mm	Gross width mm	Gross height mm	Gross area (AG) m <sup>2</sup>	Power output per collector module							
						G = 1000 W/m <sup>2</sup>							
						Tm-Ta							
						0 K	10 K	30 K	50 K	70 K			
Kairos CF 2.0-1 RF	1.83	2 004	1 004	78	2.01	1 448	1 372	1 201	1 007	790			
Performance test method							Glazed liquid heating collector - steady state - indoor						
Performance parameters related to aperture		$\eta_0$	a1	a2									
Units		-	W/(m <sup>2</sup> K)	W/(m <sup>2</sup> K <sup>2</sup> )									
Test results - Flow rate and fluid see note 1		0.790	4.010	0.016									
Bi-directional incidence angle modifiers?		No <i>K<math>\theta</math> values are obligatory for 50°.</i>											
Incidence angle modifiers K $\theta(\theta)$		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°		
Incidence angle modifier not bi-directional - leave fields blank		K $\theta(\theta)$	1.00	0.99	0.98	0.96	0.93	0.87	0.75	0.38	0.00		
Stagnation temperature - Weather conditions see note 2							Tstg		190		°C		
Effective thermal capacity							ceff = C/Ag		5.14		kJ/(m <sup>2</sup> K)		
Max. intended operation temperature - see note 3							Tmax,op		190		°C		
Max. operation pressure - see note 3							pmax,op		600		kPa		
Pressure drop table - for a collector family, the values shall be for the module with highest $\Delta P$ per m <sup>2</sup> aperture area													
Flow rate	kg/(s m <sup>2</sup> )	0.005	0.010	0.015	0.020	0.025	0.030	0.035	0.040	0.045	0.050		
Pressure drop, $\Delta P$	Pa	54	120	200	293	399	519	651	797	956	1127		
Optional weather data	Location					Link							
Testing Laboratory		TÜV Rheinland Energie und Umwelt GmbH											
Website		www.tuc.com/st											
Test report id. number		21229451.003					Date of test report		2015.12.02				
During the test GDIF/GTOT was always between		0.13	and		0.71								
Comments of testing laboratory:													
Note 1	Flow rate	0.022	kg/(s m <sup>2</sup> )	Fluid	Water								
Note 2	Irradiance, G = 1000 W/m <sup>2</sup> ; Ambient temperature, Ta=30 °C												
Note 3	Given by manufacturer												
 Genau. Richtig.  TÜV Rheinland Energie und Umwelt GmbH Am Grauen Stein 51105 Köln													
Datasheet version: 4.05, 2013-11-07													
<b>DIN CERTCO • Albainstraße 56 • 12103 Berlin, Germany</b> <b>Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de</b>													



Annual collector output based on EN 12975 Test Results, annex to Solar KEYMARK Certificate	Licence Number	011-7S2615 F
	Issued	02.12.2015

Annual collector output kWh/module													
Collector name	Location and collector temperature (T <sub>m</sub> )												
	Athens			Davos			Stockholm			Würzburg			
	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	
Kairos CF 2.0-1 RF	2 271	1 563	963	1 696	1 124	657	1 253	786	445	1 364	847	472	

Collector mounting: Fixed or tracking	Fixed; slope = latitude - 15° (rounded to nearest 5°)
---------------------------------------	---

Overview of locations				
Location	Latitude °	G <sub>tot</sub> kWh/m <sup>2</sup>	T <sub>a</sub> °C	Collector orientation or tracking mode
Athens	38	1 765	18.5	South, 25°
Davos	47	1 714	3.2	South, 30°
Stockholm	59	1 166	7.5	South, 45°
Würzburg	50	1 244	9.0	South, 35°

G <sub>tot</sub>	Annual total irradiation on collector plane	kWh/m <sup>2</sup>
T <sub>a</sub>	Mean annual ambient air temperature	°C
T <sub>m</sub>	Constant collector operating temperature (mean of in- and outlet temperatures)	°C

The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool ScenoCalc. The collector output is calculated hour by hour according to the efficiency parameters from the Keymark test using constant collector operating temperature (T<sub>m</sub>). A detailed description of the calculations is available at <http://www.sp.se/en/index/services/solar/ScenoCalc/Sidor/default.aspx>.