


Annex to Solar Keymark Certificate						Licence Number		011-7S3033 P			
						Date issued		2023-08-15			
						Issued by		DINCertco			
Licence holder		Use All Energy B.V.				Country		Netherlands			
Brand (optional)						Web		www.useallenergy.nl			
Street, Number		Kastanjestraat 6.				E-mail		info@useallenergy.nl			
Postcode, City		7497 NX Bentelo				Tel		+31 6 20 74 10 89			
Collector Type						Flat plate collector					
Collector name	Gross area (A _G) m ²	Gross length mm	Gross width mm	Gross height mm	Power output per collector G _b = 850 W/m ² , G _d = 150 W/m ² & u = 1.3 m/s θ _m - θ _a						
					0 K W	10 K W	30 K W	50 K W	70 K W	50 K W	
UAE SHMP-23-1	1.95	1 722	1 134	30	615	364	0	0	--	0	
Power output per m ² gross area					315	187	0	0	--	0	
Performance parameters test method		Steady state - indoor									
Performance parameters (related to A _G)		η _{0, b}	a1	a2	a3	a4	a5	a6	a7	a8	Kd
Units		-	W/(m ² K)	W/(m ² K ²)	J/(m ³ K)	-	J/(m ² K)	s/m	W/(m ² K ⁴)	W/(m ² K ⁴)	-
Test results		0.283	14.79	0.000	1.137	0.00	19 794	0.019	0.00	0.0E+00	1.00
Incidence angle modifier test method			Quasi dynamic - outdoor								
Incidence angle modifier		Angle	10°	20°	30°	40°	50°	60°	70°	80°	90°
Transversal		K _{θT, coll}	1.00	0.99	0.99	0.98	0.96	0.92	0.85	0.62	0.00
Longitudinal		K _{θL, coll}	1.00	0.99	0.99	0.98	0.96	0.92	0.85	0.62	0.00
Heat transfer medium for testing						Water					
Flow rate for testing (per gross area, A _G)						dm/dt	0.027	kg/(sm ²)			
Maximum temperature difference during thermal performance test						(θ _m -θ _a) _{max}	20	K			
Standard stagnation temperature (G = 1000 W/m ² ; θ _a = 30 °C)						θ _{stg}	70	°C			
Maximum operating temperature						θ _{max, op}	80	°C			
Maximum operating pressure						p _{max, op}	400	kPa			
Testing laboratory		TÜV Rheinland Solar GmbH				www.tuv.com/solar					
Test report(s)		21252546.001 DE23QEV9 001				Dated		08.10.2021 15.08.2023			
Comments of testing laboratory						Draft Ver. 6.2 (22.09.2021)					
Thermal performance parameters are given for the PV-module working with max. electrical power output ('MPP mode'). The Certificate is only valid in combination with Longi PV module LR4-60HIH 350...380M (IEC certificate Z2 099333 0062 Rev. 07 by TÜV Süd)						 <p>TÜV Rheinland Solar GmbH Am Grauis Stein 51105 Köln</p>					
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de											

Annex to Solar Keymark Certificate						Licence Number		011-7S3033 P					
Supplementary Information						Issued		2023-08-15					
Gross Thermal Yield in kWh/collector at mean fluid temperature ϑ_m													
Standard Locations		Athens			Davos			Stockholm			Würzburg		
Collector name	ϑ_m	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C	25°C	50°C	75°C
UAE SHMP-23-1		845	11		174	0		224	0		275	1	
Gross Thermal Yield per m ² gross area		433	6	--	89	0	--	115	0	--	141	1	--
Annual efficiency, η_a		25%	0%	--	5%	0%	--	10%	0%	--	11%	0%	--
Fixed or tracking collector		Fixed (slope = latitude - 15°; rounded to nearest 5°)											
Annual irradiation on collector plane		1765 kWh/m ²			1630 kWh/m ²			1166 kWh/m ²			1244 kWh/m ²		
Mean annual ambient air temperature		18.5°C			3.2°C			7.5°C			9.0°C		
Collector orientation or tracking mode		South, 25°			South, 30°			South, 45°			South, 35°		
The collector is operated at constant temperature ϑ_m (mean of in- and outlet temperatures). The calculation of the annual collector performance is performed with the official Solar Keymark spreadsheet tool Scenocalc Draft Ver. 6.2 (22.09.2021). A detailed description of the calculations is available at http://www.estif.org/solarkeymarknew/													
Additional Information													
Collector heat transfer medium								Water-Glycole					
The collector is deemed to be suitable for roof integration								Yes					
The collector was tested successfully under the following conditions:													
Climate class (A+, A, B or C)								A		--			
G (W/m ²) >		1000		ϑ_a (°C) >		20		H _x (MJ/m ²) >		600			
Maximum tested positive load								2400		Pa			
Maximum tested negative load								2400		Pa			
Hail resistance using ice balls (diameter)								35		mm			
Additional collector attribute(s)													
Using external power source(s) for normal operation						No		Active or passive measure(s) for self-protection				No	
Co-generating thermal and electrical power						Yes		Façade collector(s)				No	
Energy Labelling Information						Additional Informative Technical Data							
		Reference Area, A _{sol} (m ²)			Hydraulic Designation Code			Aperture Area, A _a (m ²)					
UAE SHMP-23-1		1.95			24-H-1234B-A:6.5,1020-C:12,1635			1.95					
Data required for CDR (EU) No 811/2013 - Reference Area A _{sol}		Collector efficiency (η_{col})			-20%			Data required for CDR (EU) No 812/2013 - Reference Area A _{sol}					
Remark: Collector efficiency (η_{col}) is defined in CDR (EU) No 811/2013 as collector efficiency of the solar collector at a temperature difference between the solar collector and the surrounding air of 40 K and a global solar irradiance of 1000 W/m ² , expressed in % and rounded to the nearest integer. Deviating from the regulation η_{col} is based on reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806:2017.		Zero-loss efficiency (η_0)			0.32			--					
		First-order coefficient (a ₁)			12.86			W/(m ² K)					
		Second-order coefficient (a ₂)			0.000			W/(m ² K ²)					
		Incidence angle modifier IAM (50°)			0.97			--					
Remark: The data given in this section are related to collector reference area (A _{sol}) which is aperture area for values according to EN 12975-2 or gross area for ISO 9806. Consistent data sets for either aperture or gross area can be used in calculations like in the regulation 811 and 812 and simulation programs.													
DIN CERTCO • Alboinstraße 56 • 12103 Berlin, Germany													
Tel: +49 30 7562-1131 • Fax: +49 30 7562-1141 • E-Mail: info@dincertco.de • www.dincertco.de													